



## Features

- Hinged-camp
- Regged construction
- Counter measures for FCC,VD
- EMI/RFI suppression

## Applications

- Interface/data line cables:
- Computers, Peripherals, terminals
- Equipment and data terminals

## Electrical Characteristics

Part Number	Cable Dia. Mm Max	Z 25MHz	Z 100MHz	Part Number	Cable Dia. Mm Max	Z 25MHz	Z 100MHz	Part Number	Cable Dia. Mm Max	Z 25MHz	Z 100MHz
SF-35A	3.5	90	130	SF-90A	9.0	60	135	SF-130A	13.0	110	230
SF-35B	3.5	55	130	SF-90B	9.0	60	135	SF-130B	13.0	110	230
SF-50	5.0	60	130	SF-100A	10.0	90	190	SF-130C	13.0	120	200
SF-60	6.0	120	230	SF-100B	10.0	35	70	SF-140A	13.6	30	60
SF-65	6.5	120	240	SF-110A	11.0	120	230	SF-80A	8.0	35	80
SF-70A	7.0	35	60	SF-110B	11.0	120	230	SF-80B	8.0	55	120
SF-70B	7.0	35	60	SF-110C	11.4	40	90	SF-40F	4.0	90	180

SF-35A	SF-35B	SF-50	SF-60	SF-65	SF-70A	SF-70B
SF-90A	SF-90B	SF-100A	SF-100B	SF-110A	SF-110B	SF-110C
SF-130A	SF-130B	SF-130C	SF-140	SF-80A	SF-80B	SF-40F