

10/100 Base-T Quad Port Transformer

- Cw/w: 50PF Typ @ 100KHz, 0.2V
- Polarity: 1-40, 3-38, 6-35, 8-33, 11-30, 13-28, 16-25, 18-23 In-Phase
- LL: 0.5uH Max @ 100KHz, 0.2V
- DCR: 0.9Ω Max
- Operating Temp: 0°C to +70°C


Electrical Specifications @25°C

Part Number	OCL(uH Min) @ 100kHz, 200mV	Turns Ratio chip: cable (±5%)	Insertion Loss (dB Max)		Return Loss (dB Min)		
	With 8mA DC Bias		0.3-100MHz	0.3-30MHz	40MHz	50MHz	60-80MHz
MHTA-4001S	350	1CT:1CT(TX)/1CT:1CT(RX)	-1.1	-18	-14.4	-13.1	-12

Electrical Specifications @25°C

Part Number	Common Mode Rejection (dB Min)			Cross Talk (dB Min)		Isolation HI-POT (Vrms) 60S
	0.3-30MHz	60MHz	80-100MHz	0.3-30MHz	60-100MHz	
MHTA-4001S	-40	-35	-30	-42	-33	1500

MECHANICAL



Dimensions: inch (mm)
Unless otherwise specified, all tolerances are ±0.010(0.25)

SCHEMATICS

