

100/1000 Base T Gigabit Dual Port Transformer

- Polarity: 2-47, 5-44, 8-41, 11-38, 14-35, 17-32, 20-29, 23-26 In-Phase
- LL: 0.5uH Max @ 100KHz, 200mV
- DCR: 0.9Ω Max
- Cw/w: 25PF TYP @ 100KHz, 200mV
- Operating Temp: 0°C to +70°C


► Electrical Specifications @25°C

Part Number	OCL(uH Min) @ 100kHz, 0.2V With 8mA DC Bias	Turns Ratio chip: cable (±5%)	Insertion Loss (dB Max)		Return Loss (dB Min)			
			1-100MHz	1-30MHz	40MHz	50MHz	60-80MHz	100MHz
MGSC-4802S	350	1CT:1CT(TX)/1CT:1CT(RX)	-1.0	-16	-14.4	-13.1	-12	-10

► Electrical Specifications @25°C

Part Number	Differential to Common Mode Rejection (dB Min)			Cross Talk (dB Min)			Isolation HI-POT (Vrms) 60S
	1-30MHz	60MHz	100MHz	30MHz	60MHz	100MHz	
MGSC-4802S	-40	-35	-30	-40	-35	-30	1500

► MECHANICAL



Dimensions: mm(inch)
Unless otherwise specified, all tolerances are±0.25(0.010)

► SCHEMATICS

